

- Shrink Temp. 347°F
- Mil-I-DTL-23053/13
- Flame Retardant
- Resistant to Highly Corrosive Acids, Fluids, Fuels, & Solvents
- High Operating Temp.
  392°F for Extreme Working Conditions

## 2:1 Viton® - Flexible Heatshrink Tubing

Viton® is a rubber-like, highly fluid-resistant, flame retardant flouro-elastomer heat-shrinkable tubing with high solvent resistance. The product is recommended for bundling, harnessing, and environmental protection within engine compartments.

	Nominal		Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available	Lbs/
ı	Size				Bulk Spool	Shop Spool	Colors	100′
	1/8"	H2V0.13BK	3.2mm	1.6mm	200′	100′	Black (BK)	1.26
1	3/16"	H2V0.19BK	4.8mm	2.4mm	200′	100′	Black (BK)	1.45
1	1/4"	H2V0.25BK	6.4mm	3.2mm	200′	100′	Black (BK)	1.68
	3/8"	H2V0.38BK	9.5mm	4.7mm	100′	100′	Black (BK)	2.27
1	1/2"	H2V0.50BK	12.7mm	6.4mm	100′	50′	Black (BK)	2.29
	5/8"	H2V0.63BK	16.0mm	8.0mm	100′	50′	Black (BK)	2.50
1	3/4"	H2V0.75BK	19.1mm	9.5mm	100′	50′	Black (BK)	4.14
1	7/8"	H2V0.88BK	22.4mm	11.0mm	100′	25′	Black (BK)	4.83
1	1"	H2V1.00BK	25.4mm	12.7mm	100′	25′	Black (BK)	5.73
1	1 1/4"	H2V1.25BK	31.7mm	15.7mm	100′	25′	Black (BK)	8.20
1	1 1/2"	H2V1.50BK	38.1mm	19.1mm	100′	25′	Black (BK)	8.80
l	2"	H2V2.00BK	50.8mm	25.4mm	50′	25′	Black (BK)	13.40

Viton® is a registered trademark of DuPont Performance Elastomers.



Dual wall adhesive-lined polyolefin heatshrink tubing is ideal for producing strong, weather tight seals on any heatshrink installation. During the application of heat from a heat gun or other heat source, the inner adhesive wall melts and flows, creating an adhesion layer to ensure a snug fit to your harness or connector. Adhesive lined heatshrink comes in 2:1, 3:1, 4:1, and 6:1 shrink ratio, and it is available in 4' sticks.

1 (833) SLEEVING www.techflex.com

Moisture, & Corrosion

**Connectors & Splices** 

• Excellent Electrical

Protects from Fluids,

**Properties**