

- **Temp. -67 to 230°F**
- **Maximum Volt: 1000V**
- **UV-Resistant**
- **Ribbed Liner on Inside Provides Better Grip and Airtight Sealing**



3:1 Heatshrink Boots Provide Cable Termination From Water, Moisture, Air, And Dirt

Specially designed for quick sealing and maximum strain relief, Shrinkflex® Boots provide complete insulation and protection when transitioning from single to multiple cables. An innovative, heat-activated interior adhesive coating forms a water-tight seal and helps these boots conform snugly to conduits and cable jackets. Suitable for indoor and outdoor usage.

Nominal Size	Part #	# Of Cores	Length	Bulk Box Put Up/Pcs.	Shop Box Put Up/Pcs.	Available Colors	Lbs/ 10Pcs.
1"	HB21.00BK	2	2.2"	10	2	Black (BK)	0.13
1 1/5"	HB21.20BK	2	3.7"	10	2	Black (BK)	0.16
1 1/2"	HB21.50BK	2	5"	10	2	Black (BK)	0.20
2 1/2"	HB22.50BK	2	4.6"	10	2	Black (BK)	0.65
1 1/2"	HB31.50BK	3	4.3"	10	2	Black (BK)	0.82
2 1/2"	HB32.50BK	3	6.5"	10	2	Black (BK)	1.27
1 1/2"	HB41.50BK	4	4.1"	10	2	Black (BK)	0.41
2"	HB42.00BK	4	6"	10	2	Black (BK)	1.03
3"	HB43.00BK	4	7"	10	2	Black (BK)	1.92

- **Temp. -67 to 230°F**
- **Shrink Temp. 248°F**
- **Typically Used in Conjunction with Heatshrink Tubing**



2:1- 3:1 Heatshrink End Caps

Protect the whole cable with Shrinkflex® End Caps! Shrinkflex® End Caps insulate and seal off wire and splice terminations, adding critical protection against abrasion, moisture, fraying, chemicals, and corrosion. Designed to be used in tandem with Shrinkflex® heatshrink, these caps are adhesive lined in order to bond with the heatshrink they overlap. Well-suited for automotive, networking, and electrical applications.

Nominal Size	Part #	Shrink Ratio	Length	Bulk Box Put Up/Pcs.	Available Colors	Lbs/ 10Pcs.
3/8"	HAC0.38BK	2:1	1.30"	10	Black (BK)	0.05
1/2"	HAC0.50BK	3:1	1.80"	10	Black (BK)	0.06
3/4"	HAC0.75BK	3:1	2.55"	10	Black (BK)	0.12
1"	HAC1.00BK	3:1	2.80"	10	Black (BK)	0.18
1 1/2"	HAC1.50BK	3:1	3.40"	10	Black (BK)	0.43
2"	HAC2.00BK	2:1	4.30"	10	Black (BK)	0.91
3"	HAC3.00BK	2:1	5.10"	10	Black (BK)	1.60
4"	HAC4.00BK	2:1	6.10"	10	Black (BK)	3.04
5"	HAC5.00BK	2:1	6.10"	10	Black (BK)	4.30