


Most Advanced Hose **Protection Solution**

DURA FLEX PROFESSIONAL (DPN) provides tough hose protection in two ways. First, per the ISO 6945 spec, DPN's unique 80 mil thick tubular weave design will withstand up to 13,000 abrasion cycles without wearing through the fabric at any location.

Additionally, the exceptionally smooth inner wall provides easy installation and minimizes any internal abrasion problems. The tightly woven nylon construction is extremely flexible and resists chemical and ultraviolet degradation. Dura-Flex Professional cuts with a scissor, and installs quickly and easily. DPN is perfect for industrial and construction applications where adequate protection is needed.



- Heavy Duty, 80 Mil **Wall Thickness**
- ISO 6945 Certified
- Professional Grade Construction
- Smooth Inner Wall **Prevents Internal Abrasion Damage**
- Nylon Construction Resists UV, Salt, Chemicals, Vermin, and Rot



your thickest protection for the longest wear



Techflex® Dura Flex products add increased safety in confined spaces such as mines



Whatever your hose or application, DPN will provide an extra level of protection from cuts, abrasion, and UV damage.



Nominal	Part	Wall	Standard Spool Put-Ups		Available	Lbs/	
Size	#	Thickness	Bulk Spool	Shop Spool	Colors	100′	
0.75"	DPN0.75BK	.08″	100′	50′	Black (BK)	4.43	
0.93"	DPN0.93BK	.08″	100′	50′	Black (BK)	5.51	
1.13"	DPN1.13BK	.08″	100′	50′	Black (BK)	7.15	
1.25"	DPN1.25BK	.08″	100′	50′	Black (BK)	7.44	
1.35"	DPN1.35BK	.08″	100′	50′	Black (BK)	8.02	
1.43"	DPN1.43BK	.08″	100′	50′	Black (BK)	8.32	
1.63"	DPN1.63BK	.08″	100′	50′	Black (BK)	9.53	
1.81"	DPN1.81BK	.08″	100′	50′	Black (BK)	10.71	
2.19"	DPN2.19BK	.08″	100′	50′	Black (BK)	12.31	
2.38"	DPN2.38BK	.08″	100′	50′	Black (BK)	13.70	
2.63"	DPN2.63BK	.08″	100′	50′	Black (BK)	14.83	
2.88"	DPN2.88BK	.08″	100′	50′	Black (BK)	17.30	
3.13"	DPN3.13BK	.08″	50′	25′	Black (BK)	18.04	
3.38"	DPN3.38BK	.08″	50′	25′	Black (BK)	20.11	
3.63"	DPN3.63BK	.08″	50′	25′	Black (BK)	21.60	
4.00"	DPN4.00BK	.08″	50′	25′	Black (BK)	23.52	

ISO	
6945	

	Abrasion Resistance											
	630	950	2,500	3,500	4,400	8,500	*13,000					
HIGH						EXTREMELY HIGH						

1 (833) SLEEVING www.techflex.com