



FR SILICONE COATED FIBERGLASS - GRADE A

**UL RECOGNIZED # E329694 • RATED TO 392°F, CLASS H • MIL-I-003190/6
RESISTS ACIDS & ALIPHATIC HYDROCARBONS • NEMA TF-1-TYPE 6 • ASTM D372**

FLAME RETARDANT SILICONE FLEX GLASS (SF) sleeving is an extremely flexible braided fiberglass sleeve coated with a flame retardant elastomeric silicone rubber sheath. The unique self-fitting construction allows SF sleeving to expand slightly for easy installation, and provides a snug fit for minimum movement and reduced internal abrasion. SF sleeving is rated to 392°F. (Class H), is abrasion resistant, and maintains its flexibility in low temperature environments. It is available in a very wide range of sizes, and is ideal for use in appliance assemblies, wire harnesses, transformer leads, power supplies, motor coil and heater leads.

SIZING CHART

Nominal Size	Diameter	Part #	Grade	Wall Thickness	*Put-Ups		Available Colors	Lbs/ 100'
					M	L		
24	.022"	SFAG.24	A		250'	500'	3	
22	.027"	SFAG.22	A		250'	500'	3	
20	.034"	SFAG.20	A		250'	500'	3	
18	.042"	SFAG.18	A		250'	500'	3	
16	.053"	SFAG.16	A		250'	500'	3	
14	.066"	SFAG.14	A		250'	500'	3	
12	.085"	SFAG.12	A		100'	250'	3	
10	.106"	SFAG.10	A		100'	250'	3	
9	.118"	SFAG.09	A		100'	250'	3	
8	.133"	SFAG.08	A		100'	250'	3	
7	.148"	SFAG.07	A		100'	250'	3	
6	.166"	SFAG.06	A		100'	250'	3	
5	.186"	SFAG.05	A		100'	250'	3	
4	.208"	SFAG.04	A		100'	250'	3	
3	.234"	SFAG.03	A		100'	250'	3	
2	.263"	SFAG.02	A		100'	250'	3	
1	.294"	SFAG.01	A		50'	100'	3	
0	.330"	SFAG.00	A		50'	100'	3	
3/8"	.375"	SFA0.38	A		50'	100'	3	
7/16"	.438"	SFA0.44	A		50'	100'	3	
1/2"	.500"	SFA0.50	A		50'	100'	3	
5/8"	.625"	SFA0.63	A		50'	100'	3	
3/4"	.750"	SFA0.75	A		50'	100'	3	
7/8"	.875"	SFA0.88	A		50'	100'	3	
1"	1.00"	SFA1.00	A		50'	100'	3	
1 1/4"	1.25"	SFA1.25	A		NA	100'	3	
1 1/2"	1.50"	SFA1.50	A		NA	100'	3	

*Put-Ups: "M" = Shop Spool and "L" = Bulk Spool

