



BRAIDED META ARAMID (NOMEX®) LACING TAPE A-A-52084 TYPE V · 2 FINISHES: A-NO FINISH AND C-SYNTHETIC RUBBER NON FLAMMABLE

While cable ties are the most common method of wire dressing, there is an alternate method known as cable lacing. This method has been used on aircraft, ships, and military equipment for many years. This lacing tape meets Military Specification MIL-T-43435 and is produced from continuous filament electrical grade glass (E-glass). It has a minimal fiber to fiber abrasion, very low elongation, and extremely high temperature performance. Lacing tape lasts longer than cable ties. Cable ties turn brittle and degrade over time due to environmental exposure and loss of plasticizers. A roll of lacing tape can manage any size cable bundle, from a couple of 22AWG wires to a fistful of heavy power cables. Cable ties leave a sharp edge where the tail was cut off that can snag or get hung up. Some applications such as aerospace and aviation may specify laced harnesses as a design requirement. Lacing tape is ideal for lashing wires or cables to ladder bars, conduit and other wire management solutions. Unlike cable ties, the insulation on wires bundled with lacing tape has less chance of cold flowing and shorting. No sharp edges to cut installer's hands when reaching into a tightly packed wiring cavity.

SIZING CHART

Part #	Mil Spec Size	Break Strength	Finish	Width		Thickness		Available Colors	Bulk Spool	Lbs/ Spool
				Min	Max	Min	Max			
LT5-S1-FA-NT	1	85 lbs.	A	.180"	.220"	.013"	.019"	NT	750'	0.75
LT5-S2-FA-NT	2	50 lbs.	A	.099"	.121"	.011"	.017"	NT	750'	0.40
LT5-S3-FA-NT	3	35 lbs.	A	.068"	.083"	.009"	.015"	NT	1,500'	0.45
LT5-S4-FA-NT	4	25 lbs.	A	.050"	.061"	.007"	.013"	NT	1,500'	0.35
LT5-S1-FC-NT	1	85 lbs.	C	.180"	.220"	.013"	.019"	NT	750'	0.85
LT5-S2-FC-NT	2	50 lbs.	C	.099"	.121"	.011"	.017"	NT	750'	0.45
LT5-S3-FC-NT	3	35 lbs.	C	.068"	.083"	.009"	.015"	NT	1,500'	0.50
LT5-S4-FC-NT	4	25 lbs.	C	.050"	.061"	.007"	.013"	NT	1,500'	0.40

MIL FINISHES

Finish A	No Finish
Finish C	Synthetic Elastomer (Rubber) Finish





FEATURES

Material	Meta Aramid (Nomex®)
Grade	LT5
Wall Thickness	Refer To Table
Mil Spec	A-A-52084 MIL-T-43435 TYPE V
Drawing Number	TF001LT5-WD
Cutting	Scissors
Usage	Suitable For Critical Aircraft Harness Applications

COLORS



Natural (NT)

OPERATING TEMPERATURES

Melt Point	700°F / 371°C
Maximum Continuous	500°F / 260°C
Minimum Continuous	-67°F / -55°C

FLAMMABILITY

Rating	Non Flammable
--------	---------------

DETAIL



Fiberglass Lacing Tape